741	41-6a-1120, or a device used exclusively on stationary rails or tracks.
742	Section 4. Section 41-6a-1626 is amended to read:
743	41-6a-1626. Mufflers Prevention of noise, smoke, and fumes Air pollution
744	control devices.
745	(1) (a) A vehicle shall be equipped, maintained, and operated to prevent excessive or
746	unusual noise.
747	(b) A motor vehicle shall be equipped with a muffler or other effective noise
748	suppressing system in good working order and in constant operation.
749	(c) A person may not use a muffler cut-out, bypass, or similar device on a vehicle.
750	(2) (a) [Except while the engine is being warmed to the recommended operating
751	temperature, the] The engine and power mechanism of a gasoline-powered $\hat{\mathbf{H}} \rightarrow [\underline{\text{or diesel-powered}}]$
751a	← Ĥ
752	motor vehicle may not emit visible contaminants during operation[-] unless:
753	(i) the engine of the motor vehicle is being warmed to the recommended operating
754	temperature; or
755	(ii) the motor vehicle is exempt from an emissions inspection under Section
756	<u>41-6a-1642</u> Ĥ→ [<u>or 41-6a-1644</u>] ←Ĥ .
757	(b) (i) As used in this Subsection (2)(b), "heavy tow" means a tow that exceeds the
758	vehicle's maximum tow weight.
759	(ii) A diesel engine manufactured on or after January 1, 2008, may not emit visible
760	contaminants during operation:
761	(A) except while the engine is being warmed to the recommended operating
762	temperature or under a heavy tow; or
763	(B) unless the diesel engine is in a vehicle with a manufacturer's gross vehicle weight
764	rating in excess of 26,000 pounds.
765	(iii) A diesel engine manufactured before January 1, 2008, may not emit visible
766	contaminants of a shade or density that obscures a contrasting background by more than 20%,
767	for more than five consecutive seconds:
768	(A) except while the engine is being warmed to the recommended operating
769	temperature or under a heavy tow; or
770	(B) unless the diesel engine is in a vehicle with a manufacturer's gross vehicle weight
771	rating in excess of 26,000 pounds.

- 25 -